


抱き合わせクランプ

☆ボルト・ナット付き(各2個)



鉄製(メッキ仕上げ・黒塗装)

商品番号	使用可能パイプ径 (許容範囲)	締め付け幅 (W)	ボルト穴径 (dφ)
91-051	50.0~57.0	30.0	11.0
91-060	58.0~64.7	30.0	11.0
91-L060	58.0~64.7	45.0	11.0
91-070	65.0~74.0	30.0	11.0
91-075	75.0~79.2	35.0	11.0
91-080	80.0~85.5	40.0	11.0
91-H080	80.0~84.0	33.0	11.0
91-M089	88.0~91.0	43.0	11.0
91-094	90.0~100.0	40.0	11.0
91-101	101.0~107.0	40.0	11.0
91-L101	101.0~107.0	60.0	11.0
91-109	108.0~118.5	35.0	11.0
91-M114	114.0~120.0	43.0	11.0

ステンレス製(SUS304)

商品番号	使用可能パイプ径 (許容範囲)	締め付け幅 (W)	ボルト穴径 (dφ)
92-051	50.0~57.0	30.0	11.0
92-070	65.0~74.0	30.0	11.0
92-080	80.0~85.5	40.0	11.0
92-089	86.0~89.5	30.0	11.0
92-094	90.0~100.0	40.0	11.0
92-101	101.0~107.0	40.0	11.0
92-109	108.0~118.5	35.0	11.0

吊り用 抱き合わせクランプ

鉄製

商品番号	使用するパイプ (外径)	締め付け幅 (W)	ボルト穴径 (dφ)
DJ-M065	65.0	38.0	11.0
DJ-M070	70.0	38.0	11.0
DJ-M080	80.0	32.0	11.0




帯鉄バンド

☆ボルト・ナット付き

鉄製

商品番号	締め付け幅 (W)	使用可能パイプ径	ボルト穴 (dφ)	厚み (t)
93-041	35.0	41.3	9.0	2.3
93-042	35.0	42.7	9.0	2.3
93-051	30.0	50.8	9.0	3.2
93-C051	35.0	50.8	9.0	3.2
93-060	30.0	60.5	11.0	3.2
93-C060	40.0	60.5	9.0	3.2
93-E060	35.0	60.5	9.0	4.5
93-064	35.0	64.0	11.0	4.5
93-065	30.0	65.0	11.0	3.2
93-C065	40.0	65.0	9.0	3.2
93-075	30.0	75.0	11.0	4.5
93-079	30.0	80.0	11.0	4.5
93-094	45.0	94.0	9.0	5.0
93-G094	32.0	94.0	11.0	3.5
93-097	35.0	97.0	11.0	4.5
93-101	35.0	101.6	9.0	5.0
93-110	35.0	110.0	9.0	5.0
93-127	35.0	127.0	9.0	5.0



☆窓付き商品は下記品番です。
93-051
93-E060


☆下記商品のボルト穴は、2か所になります。

93-C051 93-094
93-C060 93-101
93-C065 93-110
93-127



93-C051

帯鉄バンド



鉄製


商品番号	締め付け幅 (W)	使用可能パイプ径	ボルト径	厚み (t)	ボルト穴ピッチ (L)
CZ-C051	30.0	50.8	8.0	3.2	42.0
CZ-C060	40.0	60.5	8.0	3.2	35.0
CZ-C065	40.0	65.0	8.0	3.2	35.0

吊りバンド

☆ボルト・ナット付き

鉄製


商品番号	締め付け幅(W)	使用可能パイプ径	ボルト穴(dφ)	厚み(t)
CF-021	25.0	21.7	9.0	2.8
CF-027	25.0	27.2	9.0	2.8
CF-034	25.0	34.0	9.0	2.8
CF-042	25.0	42.7	9.0	2.8
CF-048	25.0	48.6	9.0	2.8
CF-060	25.0	60.5	9.0	2.8
CF-076	25.0	76.3	11.0	2.8
CF-089	25.0	89.1	11.0	2.8
CF-114	25.0	114.3	11.0	2.8
CF-139	32.0	139.8	11.0	4.5
CF-165	32.0	165.2	11.0	4.5



使用可能パイプ径

吊りバンド(蝶番式)

☆ボルト・ナット付き



使用可能パイプ径

鉄製


商品番号	締め付け幅(W)	使用可能パイプ径	ボルト穴(dφ)	厚み(t)
CG-017	25.0	17.9	7.0	1.8
CG-021	25.0	21.7	7.0	1.8
CG-027	25.0	27.2	7.0	1.8
CG-034	25.0	34.0	7.0	1.8
CG-042	25.0	42.7	7.0	1.8
CG-048	25.0	48.6	7.0	1.8
CG-060	25.0	60.5	9.0	1.8
CG-076	25.0	76.3	9.0	2.3
CG-089	25.0	89.1	9.0	2.3
CG-101	25.0	101.6	9.0	2.3
CG-114	25.0	114.3	9.0	2.3
CG-139	32.0	139.8	11.0	3.2
CG-165	32.0	165.2	14.0	3.2
CG-216	38.0	216.3	14.0	4.5
CG-267	38.0	267.4	18.0	6.0
CG-318	50.0	318.5	18.0	6.0

ステンレス製

商品番号	締め付け幅(W)	使用可能パイプ径	ボルト穴(dφ)	厚み(t)
CH-021	25.0	21.7	7.0	2.0
CH-027	25.0	27.2	7.0	2.0
CH-034	25.0	34.0	7.0	2.0
CH-042	25.0	42.7	7.0	2.0
CH-048	25.0	48.6	7.0	2.0
CH-060	25.0	60.5	7.0	2.0
CH-076	25.0	76.3	9.0	2.3
CH-089	25.0	89.1	9.0	2.3
CH-101	25.0	101.6	9.0	2.3
CH-114	25.0	114.3	9.0	2.3
CH-139	32.0	139.8	11.0	3.0
CH-165	32.0	165.2	14.0	3.0
CH-216	32.0	216.3	14.0	3.0

U型クランプ

☆ボルト・ナット・スプリングワッシャ付き
(押さえ金具付き)



鉄製(メッキ仕上げ)

商品番号	使用可能パイプ径 (許容範囲)	内寸法 (J)	全長 (L)	ネジ切り (E)	丸棒径 (R)
95-032	29.0~31.8	33.0	60.0	25.0	8.0
95-035	32.0~35.0	36.0	68.0	30.0	8.0
95-L036	32.0~35.0	36.0	95.0	50.0	8.0
95-038	36.0~38.1	39.0	65.0	30.0	8.0
95-041	39.0~40.8	42.0	65.0	30.0	8.0
95-043	42.0~42.7	43.0	68.0	30.0	8.0
95-045	43.0~45.0	46.0	75.0	35.0	8.0
95-048	46.0~48.0	48.5	75.0	35.0	8.0
95-051	48.6~50.8	52.0	80.0	35.0	8.0
95-L051	50.0~50.8	51.0	108.0	50.0	8.0
95-054	51.0~54.0	55.0	85.0	35.0	8.0
95-057	55.0~57.0	58.0	85.0	35.0	8.0
95-060	58.0~60.5	62.0	90.0	35.0	8.0
95-L060	58.0~60.5	62.0	116.0	50.0	8.0
95-064	61.0~64.0	65.0	95.0	40.0	8.0
95-067	65.0~67.0	68.0	100.0	40.0	8.0
95-069	68.0~69.0	72.0	88.0	30.0	10.0
95-082	69.0~82.0	82.0	125.0	50.0	10.0
95-096	83.0~96.0	96.0	140.0	50.0	10.0
95-108	97.0~108.0	108.0	145.0	50.0	10.0
95-120	109.0~120.0	120.0	170.0	60.0	10.0

ステンレス製(SUS304)


商品番号	使用可能パイプ径 (許容範囲)	内径 (B)	全長 (L)	ネジ切り (E)	丸棒径 (R)
96-054	50.8~54.0	54.0	85.0	35.0	8.0
96-067	60.5~65.0	67.0	100.0	40.0	8.0

Uボルト

☆鉄製のナット・スプリングワッシャ付き(各2個)
☆押さえ金具無し

鉄製(メッキ仕上げ)

商品番号	内寸法 (J)	全長 (L)	ネジ切り (E)	丸棒径 (R)
97-015	15.0	33.0	16.0	6.0
97-019	18.0	38.0	18.0	6.0
97-024	24.0	60.0	30.0	5.0
97-L024	24.0	99.0	40.0	10.0
97-029	29.0	75.0	30.0	5.0
97-030	30.0	55.0	25.0	8.0
97-032	32.0	105.0	45.0	10.0
97-K032	33.0	60.0	25.0	8.0
97-035	36.0	85.0	30.0	6.0
97-K035	35.0	68.0	30.0	8.0
97-036	36.0	95.0	50.0	8.0
97-K038	39.0	65.0	30.0	8.0
97-039	39.0	110.0	45.0	10.0
97-K041	42.0	65.0	30.0	8.0
97-K043	43.0	68.0	30.0	8.0
97-045	45.0	125.0	50.0	10.0
97-K045	45.0	70.0	30.0	8.0
97-K048	50.0	75.0	30.0	8.0
97-051	51.0	108.0	50.0	8.0
97-K051	53.0	80.0	35.0	8.0
97-L051	51.0	130.0	50.0	10.0
97-K054	56.0	85.0	35.0	8.0
97-K057	59.0	85.0	35.0	8.0
97-060	62.0	116.0	50.0	8.0
97-K060	62.0	90.0	35.0	8.0
97-K064	65.0	95.0	35.0	8.0
97-065	65.0	140.0	50.0	10.0
97-K067	69.0	100.0	40.0	8.0
97-K069	72.0	88.0	30.0	10.0
97-079	79.0	117.0	35.0	10.0
97-L079	79.0	165.0	50.0	10.0
97-K082	82.0	125.0	50.0	10.0
97-094	94.0	175.0	50.0	10.0
97-095	92.0	127.0	35.0	10.0
97-K096	96.0	140.0	50.0	10.0
97-104	104.0	135.0	30.0	8.0
97-106	105.0	142.0	35.0	10.0
97-K108	108.0	145.0	50.0	10.0
97-116	116.0	155.0	35.0	10.0
97-K120	120.0	160.0	60.0	10.0
97-143	142.0	185.0	40.0	10.0
97-171	171.0	210.0	45.0	10.0
97-195	195.0	230.0	50.0	10.0
97-220	220.0	260.0	50.0	12.0
97-270	270.0	320.0	50.0	12.0





Uボルト

☆鉄製のナット・スプリングワッシャ付き(各2個)
☆押さえ金具は無し

ステンレス製

商品番号	内寸法 (J)	全長 (L)	ネジ切り (E)	丸棒径 (R)
90-026	26.0	105.0	45.0	8.0
90-029	29.0	56.0	24.0	8.0
90-030	30.0	64.0	30.0	10.0
90-032	32.0	109.0	50.0	8.0
90-035	35.0	62.0	25.0	8.0
90-036	36.0	69.0	30.0	10.0
90-038	38.0	110.0	50.0	8.0
90-044	44.0	60.0	30.0	8.0
90-046	46.0	78.0	30.0	10.0
90-L046	46.0	120.0	50.0	8.0
90-051	51.0	75.0	30.0	8.0
90-L051	51.0	130.0	50.0	8.0
90-052	52.0	84.0	30.0	10.0
90-K054	54.0	85.0	35.0	8.0
90-063	63.0	88.0	30.0	8.0
90-064	64.0	95.0	30.0	10.0
90-065	65.0	140.0	50.0	8.0
90-K067	67.0	100.0	40.0	8.0
90-076	80.0	117.0	35.0	10.0
90-078	78.0	104.0	30.0	8.0
90-079	79.0	160.0	50.0	8.0
90-091	91.0	127.0	35.0	10.0
90-093	93.0	180.0	50.0	8.0
90-105	105.0	142.0	35.0	10.0
90-116	116.0	155.0	35.0	10.0
90-142	142.0	185.0	40.0	10.0



クランプ ラッパ管用

鉄製

商品番号	ラッパ部外径 仕様寸法	ラッパ管
DY-07690	90.0	DV-07690
DY-094106	106.0	DV-094106
DY-113120	120.0	DV-113120





ハイトルククランプ Aタイプ

☆ホース用クランプにも使用できます。

セミステンレス・鉄製

商品番号	使用可能 パイプ径	商品 内径	締め付け幅 (W)	ボルト径 (R)
BH-029	27.0~29.0	29.0	18.0	M6
BH-031	29.0~31.0	31.0	18.0	M6
BH-034	31.0~34.0	34.0	18.0	M6
BH-037	34.0~37.0	37.0	20.0	M7
BH-040	37.0~40.0	40.0	20.0	M7
BH-043	40.0~43.0	43.0	20.0	M7
BH-047	43.0~47.0	47.0	20.0	M7
BH-051	47.0~51.0	51.0	20.0	M7
BH-055	51.0~55.0	55.0	20.0	M7
BH-059	55.0~59.0	59.0	20.0	M7
BH-063	59.0~63.0	63.0	20.0	M7
BH-068	63.0~68.0	68.0	20.0	M7
BH-079	73.0~79.0	79.0	25.0	M8
BH-085	79.0~85.0	85.0	25.0	M8
BH-091	85.0~91.0	91.0	25.0	M8
BH-097	91.0~97.0	97.0	25.0	M8
BH-104	97.0~104.0	104.0	25.0	M8
BH-112	104.0~112.0	112.0	25.0	M8
BH-121	112.0~121.0	121.0	25.0	M8
BH-130	121.0~130.0	130.0	25.0	M8



ステンレス製 (SUS304)

商品番号	使用可能 パイプ径	商品 内径	締め付け幅 (W)	ボルト径 (R)
DS-034	31.0~34.0	34.0	20.0	M7
DS-051	47.0~51.0	51.0	20.0	M7
DS-055	51.0~55.0	55.0	20.0	M7
DS-059	55.0~59.0	59.0	20.0	M7
DS-063	59.0~63.0	63.0	20.0	M7
DS-068	63.0~68.0	68.0	20.0	M7
DS-079	73.0~79.0	79.0	25.0	M8
DS-085	79.0~85.0	85.0	25.0	M8
DS-091	85.0~91.0	91.0	25.0	M8
DS-097	91.0~97.0	97.0	25.0	M8
DS-104	97.0~104.0	104.0	25.0	M8
DS-112	104.0~112.0	112.0	25.0	M8
DS-121	112.0~121.0	121.0	25.0	M8
DS-130	121.0~130.0	130.0	25.0	M8


- ☆ボルト(鉄製・メッキ)
- ☆ナット(鉄製・メッキ)
- ☆バンド(セミステンレス・SUS430)
- ☆ブリッジ(セミステンレス・SUS430)

ハイトルククランプ Bタイプ

☆ホース用クランプにも使用できます。
☆厚み0.7mm

ステンレス製(SUS304)

商品番号	使用可能 パイプ径	商品 内径	締め付け幅 (W)
88-032	32.0~54.0	54.0	16.0
88-045	45.0~67.0	67.0	16.0
88-057	57.0~79.0	79.0	16.0
88-070	70.0~92.0	92.0	16.0
88-083	83.0~105.0	105.0	16.0
88-095	95.0~118.0	118.0	16.0
88-108	108.0~130.0	130.0	16.0



半円バンド

☆架台への固定が可能です。




鉄製

商品番号	締め付け幅 (W)	使用可能 パイプ径	ボルト穴 (dφ)	厚み (t)
CM-021	24.0	21.7	11.0	2.3
CM-027	24.0	27.2	11.0	2.3
CM-034	24.0	34.0	11.0	2.3
CM-042	24.0	42.7	11.0	2.3
CM-048	24.0	48.6	11.0	2.3
CM-060	24.0	60.5	11.0	2.3
CM-076	24.0	76.3	11.0	2.3
CM-089	24.0	89.1	11.0	2.3
CM-114	24.0	114.3	11.0	2.3

ステンレス製

商品番号	締め付け幅 (W)	使用可能 パイプ径	ボルト穴 (dφ)	厚み (t)
CS-021	25.0	21.7	11.0	2.0
CS-027	25.0	27.2	11.0	2.0
CS-034	25.0	34.0	11.0	2.0
CS-042	25.0	42.7	11.0	2.0
CS-048	25.0	48.6	11.0	2.0
CS-060	25.0	60.5	11.0	2.0
CS-076	25.0	76.3	11.0	2.0
CS-089	25.0	89.1	11.0	2.0
CS-114	25.0	114.3	11.0	2.0

吊りクランプ




鉄製

商品番号	使用可能 パイプ外径	全長 (L1)	寸法 (L2)	穴径 (dφ)	穴数	幅 (W)
DC-051	50.8	122.0	15.0	9.0	2	67.0
DC-060	60.5	120.0	15.0	9.0	2	80.0
DC-065	65.0	122.0	15.0	9.0	2	85.0

クランプ(特殊型)

鉄製


商品番号	商品の内径	使用するパイプ外径	寸法 (L1)	寸法 (L2)	寸法 (L3)
DT-054	54.0	54.0	70.0	50.0	76.0
DT-064	64.0	64.0	80.0	50.0	88.0



クランプ(巻締めタイプ)


鉄製

商品番号	使用可能パイプ径	商品の内径 (B)	ボルト径
DB-058	57.0~59.0	59.0	8.0
DB-061	60.0~62.0	62.0	8.0
DB-064	63.0~65.0	65.0	8.0



スプリングバンド パイプ掛け

☆スコップ掛けにも使用できます。



ステンレス製

商品番号	使用可能丸パイプ外径(許容範囲)	寸法 (B)	寸法 (C)	寸法 (D)	寸法 (E)	ボルト穴径
BP-013	15.9	12.0	14.0	29.0	24.0	3.5
BP-022	22.2~27.2	14.5	20.0	40.0	25.0	5.0
BP-036	38.1~42.7	20.0	30.0	68.0	40.0	7.0